

Little Libraries Assembly Instructions



Little
Libraries

Step 1

Unwrap the pallet and set out the contents. Take care not to damage any of the parts.



The Large Set contains 7 pieces:

Tree (2 packages)
Rock 1
Rock 2
Bush 1
Bush 2
Bag with Hardware & Tool



The Small Set contains 5 pieces:

Tree (2 packages)
Rock 1
Bush 1
Bag with Hardware & Tool



Step 2

Assemble the Rock and Bush pieces, one at a time.

1. Unwrap the packaging containing the parts.



2. Ensure the face of the base piece, that has countersinks, is towards the floor.

Place the smaller center support section onto the base and fasten from underneath, using the bolts and Allen key provided. Only tighten the bolt 80% at this stage.



Assembled Dimensions

Tree	1200 W x 375 D x 995 H	Large Shrub	900 W x 425 D x 388 H	Small Shrub	602 W x 306 D x 265 H
Large Rock	870 W x 470 D x 335 H	Small Rock	650 W x 340 D x 267 H		

3. Slot the largest panel into place, and fasten the underneath, only tighten the bolt 80% at this stage.

4. Place the remaining sections onto the base, and secure with the bolts.

5. Now all bolts are in place, fully tighten until bolt heads are flush.



All Rock and Bush pieces are assembled this way. Repeat process for the remaining pieces.

Step 3 - Tree Assembly


1. First unwrap the large package containing the main tree sections.



2. Begin with the base piece, and stand it up on it's side, before putting the tree trunk piece against it. The counter sunk holes on the base piece are the bottom. Align the holes in the base, with the bottom of the tree trunk, and hand tighten the two bolts. Then, using the supplied allen key or a hex drill bit, fully tighten the bolts so that they are flush with the bottom of the base piece.



3. Now attach the base-trunk support (smallest piece). Align the holes in the base and tree trunk with the support piece, and starting from the base piece, hand tighten the 2 base bolts and the lower bolt on the trunk. **Leave the upper bolt out for now - the longer silver bolt will be used here on the main tree top piece has been attached.** Then, using the supplied allen key or a hex drill bit, fully tighten the bolts so that they are flush.



4. Next attach the largest tree piece (the tree top) to the tree trunk. To do this, lean the tree top piece against a wall, upside down. Then lift the tree tuck/base onto the front of the tree top, and rest the curve at the top of the tree trunk, on the corresponding shelf at the top of the tree top piece. Next, align the holes in the back of the tree top, with the tree trunk in the front. Next hand tighten all bolts, **including putting the longer silver bolt through the base, trunk, and into the top hole of the support piece.**

Then, using the supplied allen key or a hex drill bit, fully tighten the bolts so that they are flush.

